



## ARLISTA

# 4REA4

### LISTA ÁR

Ervényes: 2018. november 15-től visszavonásig

A tévedés és az előzetes értesítés nélküli változtatás jogát fenntartjuk!

Termékkód	Leírás	nettó	Bruttó
<b>DiGiCo 4REA Mainframe</b>			
<b>X-A-4REA4</b>	<b>DiGiCo 4REA4 processing engine</b> 6U Mainframe - 4 DMI slots, 3 SD-Card slots, 1 x 128128, 4 x 3232, 8 GPIO, 2 PSU 128 input channels, 48 output busses, 4 Areas with stereo LR and Solo 12 CG/VCA, 16 FX, 48 x 32 band graphic eq's, 8 Macros, Dimensions; 483(w) x 380(d) x 265(h) mm	1 848 150 Ft	2 347 151 Ft
<b>DiGiCo 4REA Controller options</b>			
<b>X-A-CON-1</b>	<b>DiGiCo Control 1 controller</b> Remote network controller. 1 dual function rotary encoder. LCD Display Wallmounted. Two versions - US (Decora) and EU/UK (MK Elements). TCP/IP & PoE compliant. Dimensions; 50(w) x 21(d) x 50(h) mm	81 400 Ft	103 378 Ft
<b>X-A-CON-6</b>	<b>DiGiCo Control 6 controller</b> Remote network controller. 6 dual function rotary encoder, 6 LCD Displays, 18 backlit softkeys Freestanding or desktop mounted. Powered by 12v 2.1A DC supply or PoE+. Dimensions; 208(w) x 88(d) x 250(h) mm	220 150 Ft	279 591 Ft
<b>X-A-CON-8</b>	<b>DiGiCo Control 8 controller</b> Remote network controller. 8 100mm motorised faders, 8 LCD Displays, 23 backlit softkeys Freestanding or desktop mounted. Powered by 12v 2.1A DC supply or PoE+. TCP/IP & PoE compliant. Dimensions; 315(w) x 88(d) x 332(h) mm	442 150 Ft	561 531 Ft
<b>X-A-88-GPIO</b>	<b>DiGiCo GPIO interface</b> 8x8 GPIO network interface. CAT5 connection. Phoenix connectivity. Freestanding or rack mounted (1U 1/2 width). TCP/IP compliant. Dimensions; 43(w) x 195(d) x 171(h) mm	153 550 Ft	195 009 Ft
<b>X-A-19RK-KIT</b>	<b>DiGiCo GPIO/ASTAR rack mount kit</b> 1U Rackmount kit for GPIO and/or ASTAR. Takes two units.	37 000 Ft	46 990 Ft



## ARLISTA

# 4REA4

### LISTA ÁR

Ervényes: 2018. november 15-től visszavonásig

A tévedés és az előzetes értesítés nélküli változtatás jogát fenntartjuk!

Termékkód	Leírás	nettó	Bruttó
<b>DiGiCo 4REA I/O Optios</b>			
<b>X-A-168</b>	<b>DiGiCo A168 stage expander I/O unit</b> Deployable stage box. 1 PSU, 2 x A3232 Cat5, 16 mic/line in, 8 line out Cascade or Redundant cable mode. Dimensions; 391(w) x 194(d) x 183(h) mm	479 150 Ft	608 521 Ft
<b>X-A-164-W</b>	<b>DiGiCo A164 wallmount expander I/O unit</b> Wallmount unit. 1 PSU, 2 x A3232 Cat5, 16 mic/line in, 4 line out IEC or hard-wired mains. Cascade or Redundant cable mode. <b>Dimensions; 210(w) x 87(d) x 250(h) mm</b>	479 150 Ft	608 521 Ft
<b>X-A-164-W-L</b>	<b>DiGiCo A164 wallmount expander I/O unit with LCD</b> Wallmount unit with LCD Display per socket, 1 PSU, 2 x A3232 Cat5, 16 mic/line in, 4 line out IEC or hard-wired mains. Cascade or Redundant cable mode. Dimensions; 210(w) x 87(d) x 250(h) mm	590 150 Ft	749 491 Ft
<b>X-A-STAR</b>	<b>DiGiCo ASTAR hub</b> Converts 1 x 128128 format into 4 x 3232 format. 5 CAT5 interfaces. Freestanding or rack mounted (1U 1/2 width). TCP/IP compliant. Dimensions; 43(w) x 195(d) x 171(h) mm	183 150 Ft	232 601 Ft